



## TAURUS FLOWMETERS

### Description

### TAR1SFM & TARG1-CFM ARGON FLOWMETER



The TAR1SFM and TARG1-CFM Taurus argon flowmeter connects to an argon gas cylinder. Its function is to measure the amount of gas passing through. It is generally used in TIG and MIG welding. The adjustment knob adjusts the flowrate and not the pressure. The flowrate is set in litres per minute. The gauge measures the inlet pressure and the tube measures the delivery flowrate.

SPECIFICATION	TARG1-CFM	TARG1-SFM
Gas	Argon	Argon
Maximum inlet pressure	23000 KPa	23000 KPa
Inlet Connection	G 5/8? B-RH	G 5/8? B-RH
Supply pressure gauge	0 – 31500 KPa	0 – 31500 KPa

---

Flow	0 – 30 Lpm	0 – 30 Lpm
Outlet connection	–	3/8? RH
Heated	No	No

## TARG1-HDFM HEAVY DUTY ARGON FLOWMETER



The TARG1-HDFM Taurus heavy duty flowmeter is manufactured from heavy duty brass which connects to an argon gas cylinder. Its function is to measure the amount of gas passing through. It is generally used in TIG and MIG welding. The adjustment knob accurately controls the flowrate but not the pressure.. The flowrate is set in litres per minute. The gauge measures the inlet pressure and the tube measures the delivery flowrate.

SPECIFICATION	TARG1-CFM
Gas	Argon
Maximum inlet pressure	23000 KPa
Inlet Connection	G 5/8? B-RH
Supply pressure gauge	0 – 31500 KPa
Flow	0 – 30 Lpm
Outlet connection	3/8? RH
Heated	No

## CO2 HEATED FLOWMETER



The Taurus CO2 heated flow meter connects to a gas cylinder. Its primary function is to heat the MIG gas mixture containing carbon dioxide and prevent it from freezing. The flowrate is measured in liters per minute and can be adjusted. The inlet pressure is indicated on the gauge.

### SPECIFICATION HEATED

Gas	Carbon Dioxide
Maximum inlet pressure	23000 KPa
Inlet Connection	BS341 – RH
Supply pressure gauge	0 – 31500 KPa
Flow	0 – 30 Lpm
Outlet connection	3/8" RH
Heated	Yes

### Product Category

1. Gas Equipment
2. Regulators

### Date Created

09 Nov 2025