



TAURUS GAS HOSES

Description

Gas hoses are transporting agents for various gases from a regulated gas source to gas equipment. TAURUS gas hoses are high-quality items with a flame retardant, polyester yarn reinforced EPDM outer cover resistant to welding sparks and flames. It is weatherproof, can be used indoors as well as outdoors and will support pressures up to 20 bar. The inner black rubber lining for oxygen and acetylene gas is manufactured from the SBR compound whilst that for LPG is from the NBR compound. TAURUS gas hoses can be used safely for cutting, welding, brazing and heating applications.

OXYGEN / ACETYLENE / LPG HOSE SPECIFICATION (BS EN ISO 3821)

DESCRIPTION	VALUE
Hose internal diameter	8 mm
Rating	Normal duty
Maximum operating pressure	2 MPa
Proof pressure	4 MPa
Maximum burst pressure	6 MPa
Working temperature range	-30°C to +60°C
Tube material (LPG)	NBR

Tube material (oxygen / acetylene) SBR
Cover material EPDM
Hose Polyester
reinforcement textile yarn

8MM HOSE

PRODUCT CODE	INNER HOSE DIAMETER	GAS	PRESSURE
GW90150			



8mm	OXYGEN	20MPa
-----	--------	-------

GW90050



8mm

ACETYLENE

20MPa

GW90200



8mm

LPG

20MPa

GW90250



	LPG /	
8mm	PROPANE –	20MPa
	EPDM	

VAGT812PVC



8mm	AIR / ARGON	800KPa
-----	-------------	--------

6MM HOSE

PRODUCT CODE	INNER HOSE DIAMETER	GAS	PRESSURE
--------------	------------------------	-----	----------

GW90140



6mm

OXYGEN

20MPa

GW90040



6mm

ACETYLENE

20MPa

VAGT811PVC



6mm AIR / ARGON 800KPa

Product Category

1. Gas Hose and Fittings
2. Gas Equipment

Date Created

09 Nov 2025