



## TAURUS GAS HOSES

### Description

Gas hoses are transporting agents for various gases from a regulated gas source to gas equipment. TAURUS gas hoses are high-quality items with a flame retardant, polyester yarn reinforced EPDM outer cover resistant to welding sparks and flames. It is weatherproof, can be used indoors as well as outdoors and will support pressures up to 20 bar. The inner black rubber lining for oxygen and acetylene gas is manufactured from the SBR compound whilst that for LPG is from the NBR compound. TAURUS gas hoses can be used safely for cutting, welding, brazing and heating applications.

### OXYGEN / ACETYLENE / LPG HOSE SPECIFICATION (BS EN ISO 3821)

DESCRIPTION	VALUE
-------------	-------

---

Hose internal diameter	8 mm
Rating	Normal duty
Maximum operating pressure	2 MPa
Proof pressure	4 MPa
Maximum burst pressure	6 MPa
Working temperature range	-30°C to +60°C
Tube material (LPG )	NBR
Tube material (oxygen / acetylene )	SBR
Cover material	EPDM
Hose reinforcement	Polyester textile yarn

## 8MM HOSE

PRODUCT CODE	INNER HOSE DIAMETER	GAS	PRESSURE
--------------	---------------------	-----	----------

GW90150



8mm

OXYGEN

20MPa

GW90050



8mm ACETYLENE 20MPa

GW90200



8mm

LPG

20MPa

GW90250



8mm

LPG /  
PROPANE –  
EPDM

20MPa

VAGT812PVC



8mm    AIR / ARGON    800KPa

## 6MM HOSE

PRODUCT CODE	INNER HOSE DIAMETER	GAS	PRESSURE
--------------	------------------------	-----	----------

GW90140



6mm

OXYGEN

20MPa

GW90040



6mm      ACETYLENE      20MPa

VAGT811PVC



6mm    AIR / ARGON    800KPa

**Product Category**

1. Gas Hose and Fittings
2. Gas Equipment

**Date Created**

09 Nov 2025