



## TAURUS GAS HOSES

### Description

Gas hoses are transporting agents for various gases from a regulated gas source to gas equipment. TAURUS gas hoses are high-quality items with a flame retardant, polyester yarn reinforced EPDM outer cover resistant to welding sparks and flames. It is weatherproof, can be used indoors as well as outdoors and will support pressures up to 20 bar. The inner black rubber lining for oxygen and acetylene gas is manufactured from the SBR compound whilst that for LPG is from the NBR compound. TAURUS gas hoses can be used safely for cutting, welding, brazing and heating applications.

### OXYGEN / ACETYLENE / LPG HOSE SPECIFICATION (BS EN ISO 3821)

DESCRIPTION	VALUE
Hose internal diameter	8 mm
Rating	Normal duty
Maximum operating pressure	2 MPa
Proof pressure	4 MPa
Maximum burst pressure	6 MPa
Working temperature range	-30°C to +60°C
Tube material ( LPG )	NBR

Tube material ( oxygen / acetylene ) SBR  
Cover material EPDM  
Hose reinforcement Polyester textile yarn

## 8MM HOSE

PRODUCT CODE	INNER HOSE DIAMETER	GAS	PRESSURE
GW90150			



8mm      OXYGEN      20MPa

GW90050



8mm      ACETYLENE      20MPa

GW90200



8mm      LPG      20MPa

GW90250



8mm

LPG /  
PROPANE –  
EPDM

20MPa

VAGT812PVC



8mm

AIR / ARGON

800KPa

**6MM HOSE**

PRODUCT CODE

INNER HOSE  
DIAMETER

GAS

PRESSURE

GW90140



6mm      OXYGEN      20MPa

GW90040



6mm      ACETYLENE      20MPa

VAGT811PVC



6mm      AIR / ARGON      800KPa

**Product Category**

1. Gas Hose and Fittings
2. Gas Equipment

**Date Created**

09 Nov 2025