



## TAURUS LPG HEATING BURNERS

# **Description**

# TAURUS LPG HEATING BURNERS



#### STANDARD BURNERS 19MM – 25MM

Standard burners for brush-type flames are available for various kinds of soft soldering and for small heating applications. The recommended working pressure is 2 bar.

PRODUCT BURNER CONSUMPTION EFFECT
CODE DIAMETER AT 4 BAR

LPG-B-19MM 19mm 240 g/h 3.1 kW



LPG-B-25MM 25mm 240 g/h 3.1 kW

#### **POWER BURNERS 32MM - 42MM**

Power burners are precision engineered and manufactured from heavy-duty, high-quality brass designed for extremely strong flames and to withstand high winds and the severest weather conditions. It is ideal for drying work pieces, preheating welding pieces, bitumen laying, detail and field torching, melting snow/ice and other demanding applications requiring a heat source. The recommended working pressure is 4 bar.

| PRODUCT<br>CODE | BURNER<br>DIAMETER | GAS<br>CONSUMPTION<br>AT 4 BAR | EFFECT  |
|-----------------|--------------------|--------------------------------|---------|
| LPG-B-29MM      | 29mm               | 2000 g/h                       | 26 kW   |
| LPG-B-32MM      | 32mm               | 3350 g/h                       | 43.5 kW |
| LPG-B-42MM      | 42mm               | 6700 g/h                       | 86 kW   |

### **Product Category**

- 1. Gas Equipment
- 2. Torch Nozzles

#### **Date Created**

09 Nov 2025