



TAURUS LPG HEATING BURNERS

Description

TAURUS LPG HEATING BURNERS



STANDARD BURNERS 19MM – 25MM

Standard burners for brush-type flames are available for various kinds of soft soldering and for small heating applications. The recommended working pressure is 2 bar.

PRODUCT CODE	BURNER DIAMETER	GAS CONSUMPTION AT 4 BAR	EFFECT
LPG-B-19MM	19mm	240 g/h	3.1 kW

LPG-B-25MM	25mm	240 g/h	3.1 kW
------------	------	---------	--------

POWER BURNERS 32MM – 42MM

Power burners are precision engineered and manufactured from heavy-duty, high-quality brass designed for extremely strong flames and to withstand high winds and the severest weather conditions. It is ideal for drying work pieces, preheating welding pieces, bitumen laying, detail and field torching, melting snow/ice and other demanding applications requiring a heat source. The recommended working pressure is 4 bar.

PRODUCT CODE	BURNER DIAMETER	GAS CONSUMPTION AT 4 BAR	EFFECT
LPG-B-29MM	29mm	2000 g/h	26 kW
LPG-B-32MM	32mm	3350 g/h	43.5 kW
LPG-B-42MM	42mm	6700 g/h	86 kW

Product Category

1. Gas Equipment
2. Torch Nozzles

Date Created

09 Nov 2025