

TAURUS PRO XP300A MIG TORCH

Description

The Taurus XP MIG torch is designed and manufactured for professional use. Serving performance, comfortable handling, and a long service life, and is manufactured from high-quality materials. The torch has a high duty cycle of 80% and its patented gas-flow technology ensures a cooler neck and tip, which, in turn, saves up to 70% on consumables and a reduction of welder’s downtime by up to 50%.

General checklist to assist with the selection of a MIG torch:

- Ensure the torch length is appropriate for the welding operation.
- Confirm that the torch connection will fit directly onto the machine.
- Use the correct-sized tip and liner for the welding wire size.
- The appropriate liner should be used for the filler wire material type.
- Ensure that the correct torch amperage for the application is available.

- Confirm that the duty cycle of the MIG torch selected is suitable for the application.

The Taurus XP300A MIG torch comes with the following;

- 1 x 300A (XP8) MIG torch
- 1 x Conical Nozzle/Shroud
- 1 x Gas Diffuser
- 1 x 1.2mm M8 Contact Tip
- 1 x M8 Tip Adaptor/Head Assembly
- 1 x Red Steel Liner

XP300A MIG TORCH REPLACEMENT CONSUMABLES

XP-M8 CONTACT TIPS



- 0.8mm [XP2003-08]
- 0.9mm [XP2003-09]
- 1.0mm [XP2003-10]
- 1.2mm [XP2003-12]

XP-M10 CONTACT TIPS



- 0.9mm [XP3003-09]
- 1.0mm [XP3003-10]
- 1.2mm [XP3003-12]
- 1.4mm [XP3003-14]
- 1.6mm [XP3003-16]

HEAD ASSEMBLY



- M8 [XP2005]
- M10 [XP3005]

GAS DIFFUSER



- Plastic [XP2004B]
- Ceramic [XP2004C]

M8 HEAT SHIELD



- Aluminium [XP2006A]
- Moulded [XP2006B]

NOZZLE



- 16mm Conical [XP2002-16]
- 13mm Tapered [XP3002-13]

XP STEEL LINERS



- Blue (0.6mm – 0.9mm) : 4m [XP2024-09.40]
- Red (1.0mm – 1.2mm) : 3m [XP2024-12.30]
- Red (1.0mm – 1.2mm) : 4m [XP2024-12.40]

Click here to see the full list of liners

Product Category

1. Mig Torches
2. Mig Torches and Accessories
3. XP Torches

Date Created
28 Oct 2025